

HORIBA APOA-370

O₃-Immission Monitor Data Sheet



Abstract

Our type approved instrument APOA-370 is a continuously operating analyzer for the determination of O₃ in ambient air. Other applications exist in different areas of the process and trace analysis.

Overview

The HORIBA instrument APOA-370 is a non dispersive UV absorption monitor (NDUV) using in the "crossflow" modulation principle. Sample gas and reference gas are alternately supplied to the measuring cell. Sample gas with eliminated O₃ concentration will be used as reference gas. This results in a low-maintenance operation and extremely stable measurements can be guaranteed. The analyzer is virtually interference-free and has an internal sample gas pump. Type approved according to EN 14625 (Continuous ambient air quality measurements in stationary use).

Features

- ✓ Approval according to EN 14625: TÜV 936/21204643/A and TÜV 000028756_03
- ✓ Continuous measurement of O₃ in ambient air
- ✓ "Cross Flow" Modulation principle for stable measurements
- ✓ Continuous compensation of light intensity
- ✓ Critical orifice for constant flow
- ✓ Pressure and temperature compensated
- ✓ Optimized components to reduce maintenance costs and power consumption
- ✓ Reduced weight design allows easier handling
- ✓ Internal sample gas pump
- ✓ Optional module for internal function control
- ✓ Large TFT touch-screen display
- ✓ Password protection against unauthorized access
- ✓ Remote software for an external operation
- ✓ High connectivity via RS232, Ethernet or analog (optional)
- ✓ Build-in alarm system for troubleshooting and predictive diagnostics
- ✓ Internal memory for different average values, calibration history and alarm history
- ✓ CF slot allows for memory expansion

Specifications

| | |
|----------------------------------|--|
| Principle | Non dispersive ultra-violet-absorption method (NDUV) |
| Application | O ₃ in Ambient air |
| Range | Standard ranges: 0-0.1/0.2/0.5/1.0 ppm; auto range ~ manual range selectable; can be operated by remote switching. Optional. Extension of range: 0-10 ppm, within 10 times range ratio; |
| Certified Range | 0- 500 µg/m ³ (0- 250 ppb) |
| Lowest Detection Limit (LDL) | 0,5 ppb (3δ) |
| Repeatability | ±1.0 % of F.S. |
| Linearity | ±1.0 % of F.S. (± 0,38% of F.S. according to type test) |
| Zero Point Drift | < LDL/Day, < LDL/Month (according to type test) |
| Span Point Drift | < LDL/Day, < 0,98 ppb/Month (according to type test) |
| Flow Rate | approx. 0,7 l/min |
| Response Time (T ₉₀) | < 75 sec. (minimum measurement range) < 64 sec. (according to type test) |
| Indication | Large TFT touch-screen display with simultaneous display of all current values, and the status information of the instrument. |
| Readings | Concentration in ppm (ppb) or mg (µg)/m ³ |
| Compensation | Pressure and temperature |
| Languages | English, German, French, and Japanese. |
| Interfaces | RS-232C (Bayern Hessen / HORIBA Protocol) Ethernet (HORIBA Protocol) |
| Options | Analog output 0-1/10 V or 0(4) - 20 mA Long-term data storage Calibration units Further options on request |
| Operating Temperature | 0-40°C Note: The sample gas has to pass through the system without condensation |
| Power | 230 VAC +/-10%, 50 Hz, ca. 100 VA |
| Dimensions | 430(B) x 550(T) x 221(H) mm (5HE) |
| Housing | 19" incl. telescopic rails |
| Mass | approx. 15 Kg |
| Standard auxiliary equipment | Delivery includes rails and mounting brackets for 19 "rack mount, switching valve for sample gas / calibration gas, potential free contacts for control of SGG |